

Basınç kademesi PN	Malzeme cinsleri					Artan sıcaklık (°C) kademelerinde çalışma basıncının (kg/cm ²) düşüşü						
	Vanalar				Cıvatalar DIN 2507	20(120)	200	250	300	350	400	
	Demir döküm	Sfero döküm	Çelik döküm	Çelik								
6	GG-20	GGG-38	—	St 37-2	4 D	6	—	—	—			
						6	5	4.5	3.6			
10	GG-20	GGG-38	GS-45	St 37-2	4 D	10	—	—	—			
						10	8	7	6			
16	GG-20	GGG-38	GS-45	St 37-2	4 D	16	—	—	—			
						16	13	11	10			
	—	—	GS-C 25	C 22 N	C 35	16	14	13	11	10	8	
25	—	GGG-38	GS-45.5	C 22 N	4 D	25	—	—	—			
						25	20	18	16			
		—	GS-C 25	15 Mo 3	24 CrMo 5	C 35	25	22	20	17	16	13
							GS-22 Mo 4	13 CrMo 44	24 CrMoV55			25
40	—	—	GS-45.5	C 22 N	4 D	40	32	28	24			
						40	—	—	—			
			GS-C 25	15 Mo 3	24 CrMo 5	C 35	40	35	32	28	24	21
							GS-22 Mo4	13 CrMo 44	24 CrMoV55			40
64	—	—	GS-C 25	C 22 N	4 D	64	36	29	24			
						64	50	45	40			
						64	—	—	—			
						64	50	45	40	36	32	
			GS-22 Mo 4	15 Mo 3	24 CrMo 5	C 35	64		64	56	50	47
							GS-17CrMo55	13 CrMo 44	24 CrMoV55			64
100	—	—	GS-C 25	C 22 N	4 D	100	80	70	60			
						100	—	—	—			
			GS-22 Mo 4	15 Mo 3	24 CrMo 5	C 35	100	80	70	60	56	50
							GS-17CrMo55	13 CrMo 44	24 CrMoV55			100
160	—	—	GS-C 25	C 22 N	C 45	160	130	112	96			
						160	—	—	—			
						160	130	112	96	90	80	
250	—	—	GS-C 25	C 22 N	C 45	250	200	175	150			
						250	—	—	—			
						250	200	175	150	140	125	